

CASTLE

LP7000-FT SPECIFICATIONS

GENERAL DATA

Power source	Propane
Load capacity in lbs	7,716 lbs
Service weight in lbs	11,155 lbs
Operator position	Seated
Mast type	Full free 3-stage mast
Towing coupling design	Drop pin in the back

PERFORMANCE

Lift speed (Full Load)	17.3 in/s
Drop speed (Full load)	≤23.6 in/s
Mast tilt angle	6°/6°
Top speed forward	6.5°/s
Top speed back	15°/s
Minimum turning radius	97"
Max grade with load	20%
Max grade without load	20%

WEIGHT

Total weight	11,155 lbs
Front axis load (Empty)	3,644 lbs
Back axis load (Empty)	6,433 lbs
Weight distribution full load front	88.80%
Weight distribution full load rear	11.20%
Weight distribution without load front	36.20%
Weight distribution without load rear	63.80%

TIRES

Tire type	Solid
Number of wheels front/ rear	2/2
Tire dimensions front	28x9-15-14
Tire dimensions rear	6.50-10-10
Tire pressure front	NONE
Tire pressure rear	NONE
Track width between tires front	39.3"
Track width between tires rear	38.2"
Brake type parking	Mechanical-Hand Lever
Brake type foot	Drum Brake

ENGINE **Hyundai L4KB**

Rated output	61hp / 2600rpm
Combustion system	Electronic Injection
Lubrication system	Fully forced pressure feed type
Displacement	2.359L
Number of cylinders/ cubic capacity	4
Max torque at engine Speed	134 ft lbs / 1,600rpm
Battery voltage v/capacity	13.5V/90Ah
Noise level in decibels	90dB

CASTLE

LP7000-FT SPECIFICATIONS

FULL FREE LIFT 3 STAGE

Max Fork Height (Top of Forks)	189"
Overall Height (Lowered)	85"
Overall Height (Extended)	235"
Free Lift	43"

EXTERIOR SPECIFICATIONS

A Lift height	189"
B Height from head guard	85"
C Lateral fork adjustment min/max	15-40"
D Length of Forks	48"
F Distance from front of forks to rear	157"
G Overall width	48"
H Mast Height (Lowered)	85"
I Tow coupling height	22"
J Max height extended top of fork	235"
K Front wheel distance from center	39"
L Rear wheel distance from center	38"
M Distance from wheel center to axis	67"
N Center front tire to fork face	19"
O Center rear tire to rear	23"
P Ground clearance to frame no load	6.7"
Q Mast tilt angle front/ rear	6°/6°
R Minimum turning radius	97"

