

GENERAL DATA

Power Type (battery)
Load capacity in lbs
Service weight in lbs
Battery compartment size
Operator position
Mast type
Towing coupling design

Lithium-iron Battery
7,700 lbs
12,364 lbs
34x25x20"
Seated
Full Free 3-stage mast
Drop pin in the back

PERFORMANCE

Lift speed (Full Load)	13 in/s
Drop speed (Full load)	≤15 in/
Mast tilt angle	6°/6°
Minimum turning radius	91"
Max grade with load	15%
Max grade without load	15%

WEIGHT

Total weight	12,364 lbs
Front axis load (Empty)	4,506 lbs
Back axis load (Empty)	7,064 lbs
Weight distribution full load front	17,108 lbs
Weight distribution full load rear	2,094 lbs
Weight distribution without load front	4,506 lbs
Weight distribution without load rear	7,064 lbs

TIRES

Tire type	Solid
Number of wheels front/ rear	2/2
Tire dimensions front	23x10-12-20
Tire dimensions rear	18x7-8-14
Tire pressure front	NONE
Tire pressure rear	NONE
Track width between tires front	42.5"
Track width between tires rear	40"
Brake type parking	Mechanical-Hand Leve
Brake type foot	Drum Brake

POWER SYSTEM

76.8V/420Ah
18kW
20.5kW
AC
AC
AC
2,600psi



É7000-LT4 SPECIFICATIONS FULL FREE LIFT 3 STAGE

Max Fork Height (Top of Forks) 189" 89" Overall Heigth (Lowered) Overall Height (Extended) 235" Free Lift 44"

EXTERIOR SPECIFICATIONS

	_
A Lift height	189"
B Height from head guard	89"
C Lateral fork adjustment min/max	15-40"
D Length of Forks	48"
E Overall width	48"
F Distance from front of forks to rear	148"
H Mast Height (Lowered)	89"
I Tow coupling height	18"
J Max height extended top of fork	235"
K Front wheel distance from center	39"
L Rear wheel distance from center	39"
M Distance from wheel center to axis	67"
N Center front tire to fork face	19"
O Center rear tire to rear	17"
P Ground clearance to frame no load	8"
Q Mast tilt angle front/ rear	6°/6°
R Minimum turning radius	93"

